

SPECIFICATION CLAUSES

Natural Clay Plaster Finishes

Worksection-style clauses for project documentation

1 · General

1.1 Scope. This worksection specifies the supply and application of Claywise Lithos natural clay plaster finishes to interior walls and ceilings, including preparation, the multi-stage application system and natural protection.

1.2 Cross references. Read this worksection with the substrate worksections (plasterboard, cement sheeting, render, masonry) and the Claywise Substrate & Preparation Guide, current edition.

1.3 Samples. Before commencing, provide a control sample panel of each specified grade, colour and texture, minimum 600 × 600 mm, on the project substrate, for approval. The approved panel sets the standard for the works and is retained on site until practical completion.

1.4 Installer. Application is by a Claywise-accredited installer holding current accreditation. Evidence of accreditation to be provided on request.

2 · Products

2.1 Manufacturer. Claywise Pty Ltd (ABN 23 674 156 864), Banksmeadow NSW. Supply is direct from Claywise or through appointed Claywise stockists only.

2.2 Product. Claywise Lithos natural clay plaster — unfired natural clays, graded marble aggregate, natural earth-oxide pigments; no added synthetic VOCs. Grade, colour and texture as scheduled in the Selections table.

2.3 Substitution. No substitution is permitted. A Claywise specification describes a system — the material, the accredited installer, and the manufacturer's support and warranty behind both. Alternative clay plasters in unaccredited hands sit outside that system and its warranty; the specification is not interchangeable.

2.4 Delivery and storage. Deliver in original sealed packaging, batch-marked. Store dry, off the ground, protected from moisture.

3 · Execution

3.1 Substrate. Substrates to be sound, dry, clean, stable and prepared in accordance with the Claywise Substrate & Preparation Guide. Do not commence until substrates conform.

3.2 System. Apply the Claywise multi-stage system as confirmed for the specified finish: mechanical slip coat; base coat(s); intermediate coat; finish coat(s) by trowel; and specified natural protection (sealer or wax). Maintain batch consistency within each continuous surface.

3.3 Workmanship. Finished surfaces to match the approved control sample in colour, texture and sheen, viewed in ambient light at normal viewing distances. Natural tonal and textural variation is a characteristic of the material, not a defect.

3.4 Protection. Protect completed surfaces from impact, abrasion and water until practical completion.

4 · Selections schedule

PROJECT / LOCATION	⟨project⟩ · ⟨rooms / surfaces⟩
GRADE	Lithos ⟨Cruda LTH·I / Terra LTH·II / Lumen LTH·III / Earth Plaster LTH·IV⟩
COLOUR	⟨Bone / Aroha Bone / Atla Mist / custom⟩
TEXTURE	⟨standard / custom — describe or reference sample⟩
PROTECTION	⟨natural sealer / wax / as recommended⟩
INSTALLER	Claywise-accredited installer — ⟨name on engagement⟩

Support

Specification support, project detailing and clause adaptation: Technical enquiries:
info@claywise.com.au · claywise.com.au · Showroom by appointment, 48/8 Jullian Close, Banksmeadow NSW 2019.

This document is provided in good faith as general guidance. Site conditions vary; the specifier and accredited installer remain responsible for assessing suitability for each project. Claywise products are supplied for application by Claywise-accredited installers only. Claywise® is a registered trademark of Claywise Pty Ltd. Values are typical, not specifications, unless stated. This document supersedes all previous editions.